

PS20 Personal Shopper

Accessories Guide





PS20 Configurations

Model	Part Number	Description	Comments
PS20-Base	PS201-R2G1NA00	PS20 Base Model, 4" Display, SE2100, 4GB RAM/16GB Flash, Android GMS, No- Camera, No-Sensors, 1YR Warranty, US/PR/Canada	Single Pack PS20 Base
PS20-Base	P2701-B7(31A600	PS20 Base Model, 4" Display, SE2100, 4GB RAM/16GB Flash, Android GMS, No- Camera, No-Sensors, 1YR Warranty, ROW	Single Pack PS20 Base
PS20-Base	PS201-B2G2CN00	PS20 Base Model, 4" Display, SE2100, 4GB RAM/16GB Flash, Android Non- GMS, No-Camera, No-Sensors, 1YR Warranty, China	Single Pack PS20 Base
PS20-Base		PS20 Base Model, 4" Display, SE2100, 4GB RAM/16GB Flash, Android GMS, No- Camera, No-Sensors, 1YR Warranty, US/PR/Canada, Pack of 10 Units	10 Pack PS20 Base
PS20-Base	$ \mathbf{K} = \mathbf{P} \mathbf{S} \mathbf{O} \mathbf{I} = \mathbf{R} \mathbf{O} \mathbf{G} \mathbf{I} \Delta \mathbf{G} \mathbf{O}$	PS20 Base Model, 4" Display, SE2100, 4GB RAM/16GB Flash, Android GMS, No- Camera, No-Sensors, 1YR Warranty, ROW, Pack of 10 Units	10 Pack PS20 Base
PS20-Base		PS20 Base Model, 4" Display, SE2100, 4GB RAM/16GB Flash, Android Non- GMS, No-Camera, No-Sensors, 1YR Warranty, China, Pack of 10 Units	10 Pack PS20 Base
PS20-Plus	PS201-PAG1NA00	PS20 Plus Model, 4" Display, SE4710+Digimarc, 4GB RAM/16GB Flash, Android GMS, Camera, Sensors, 1YR Warranty, US/PR/Canada	Single Pack PS20 Plus
PS20-Plus		PS20 Plus Model, 4" Display, SE4710+Digimarc, 4GB RAM/16GB Flash, Android GMS, Camera, Sensors, 1YR Warranty, ROW	Single Pack PS20 Plus
PS20-Plus	$ P \setminus J \cap - P \Delta (\neg J \cap N \cap O)$	PS20 Plus Model, 4" Display, SE4710+Digimarc, 4GB RAM/16GB Flash, Android Non-GMS, Camera, Sensors, 1YR Warranty, China	Single Pack PS20 Plus
PS20-Plus		PS20 Plus Model, 4" Display, SE4710+Digimarc, 4GB RAM/16GB Flash, Android GMS, Camera, Sensors, 1YR Warranty, US/PR/Canada, Pack of 10 Units	10 Pack PS20 Plus
PS20-Plus	$ K - PS J(1) - PA(-1 \Delta 6(1))$	PS20 Plus Model, 4" Display, SE4710+Digimarc, 4GB RAM/16GB Flash, Android GMS, Camera, Sensors, 1YR Warranty, ROW, Pack of 10 Units	10 Pack PS20 Plus
PS20-Plus	$ K - P < f(1) - P \Delta(3 f(1))(1)$	PS20 Plus Model, 4" Display, SE4710+Digimarc, 4GB RAM/16GB Flash, Android Non-GMS, Camera, Sensors, 1YR Warranty, China, Pack of 10 Units	10 Pack PS20 Plus

Spare batteries





Spare batteries:

PowerPrecision + Batteries provide an advanced new battery technology integrated into our newest devices bringing a higher level of intelligence to deliver maximum performance.

This battery is compatible with all PS20 configurations while using any MC18 single and 3-slot cradles:

- Compatible with PS20 only
- Compatible with Level V and Level VI power supplies
- Compatible with single and 3-slot cradles
- Supports standard and fast charging modes
- Not compatible with MC18 terminals

BTRY-PS20-35MA-01

PowerPrecision+ Lithium Ion battery, 3500 mAh, provides advanced State of Charge and State of Health, compatible with all PS20 configurations and cradles. Pack of 10 units: BTRY-PS20-35MA-10

Main features:

Information stored on each PowerPrecision+ battery:

- · Continuously updated capacity as battery ages
- Charge accepted per type of charger
- Time to fully charge and time to fully discharge
- · Elapsed time since first use
- Dynamically models the battery life based on historical usage

Supported features:

- Advanced state of health: actively measures and calculates the battery capacity under standard load conditions and temperature
- Advanced state of charge: time to empty under present usage and time to full under present charge condition

Cradle options

Single slot cradle



Single Slot Locking Cradle:

CRD-MC18-1SLOT-01

Single Slot Locking Cradle, keeps the device with display facing out. Compatible with MC18 and all configurations of PS20.

Requires: Power Supply **PWR-BGA12V108W0WW**, DC line cord and Country Specific AC line cord sold separately.

Additional accessories for single slot cradle



PWR-BGA12V108W0WW

Level VI AC/DC power supply. **AC Input:** 100-240V, 2.8A. **DC Output:** 12V, 9A, 108W <u>Requires:</u> DC line cord and country specific grounded AC line cord.

CBL-DC-394A1-01



DC Line Cord 19.5inch (0.5M) for powering one cradle from a single power supply. Supports interconnected cradles to charge maximum 6 devices depending on charging mode required.

CBL-DC-393A1-02



DC "Y" Line Cord 39.7inch (1M) for powering two cradles from a single power supply. Supports interconnected cradles to charge maximum 12 devices (up to 6 devices powered off each leg of the cable) depending on charging mode required.

CBL-DC-392A1-02



DC "Y" Line Cord 79.4inch (2M) for powering two cradles from a single power supply. Supports interconnected cradles to charge maximum 12 devices (up to 6 devices powered off each leg of the cable) depending on charging mode required.

25-66430-01R

Cradle Interconnection Cable 60 Inch (1.5M) Connects Cradles to each other to run off one power supply.

25-66431-01R



Cradle Interconnection Cable 12.6 Inch (32cm) Connects Cradles to each other to run off one power supply

Single Slot Cradle Charge Methods

Step 1: Power Supply	Step 2: Charge Mode	Step 3: DC Line Cord			
Level VI power supply PWR- BGA12V108W0WW and country specific 3-wire AC Line Cord.	Choose required charging mode.	Select one DC Cable to connect a power supply to multiple single slot cradles depending on charge mode:			
specifie o wire no Line oord.	Fast – 1.5 AMPS: MAX: 9 Single Slot	CBL-DC- 394A1-01	DC Line Cord 19.5inch (0.5M). Supports up to 6 single slot cradles.		
	Cradles/Devices	CBL-DC- 393A1-02	DC "Y" Line Cord 39.7inch (1M). Supports up to 12 single slot cradles (max 6 cradles powered off each leg of the cable)		
	Standard - 1.0 AMP: MAX: 12 Single Slot Cradles/Devices	CBL-DC- 392A1-02	DC "Y" Line Cord 79.4inch (2M). Supports up to 12 single slot cradles (max 6 cradles powered off each leg of the cable)		
	, i i i i i i i i i i i i i i i i i i i	392A1-02	12 single slot cradles (max 6 cradles powered		

Step 4: Interconnect cables

Choose the number of cradle interconnect cables required based on charge mode and following the table below.

Fast Charge Mode

9 Single Slot Cradles Maximum per power supply. No more than 6 single slot cradles can be powered off each leg if a "Y" power cable is used.

Cradle Interconnect Cable 25-66431-01R (12.6inch, 32cm)

Number of Cradles	2	3	4	5	6
# of Interconnect Cables required		2	3	4	5
Number of Cradles	7		8		9
# of Interconnect Cables required	5		6		7

Standard Charge Mode


12 Single Slot Cradles Maximum per power supply. No more than 6 single slot cradles can be powered off each leg if a "Y" power cable is used.



Cradle Interconnect Cables: 25-66431-01R (12.6inch, 32cm)

Number of Cradles	2	3		4	5	6
# of Interconnect Cables required	1	2	:	3	4	5
Number of Cradles	7	8	9	10	11	12
# of Interconnect Cables required	5	6	7	8	9	10

Single Slot Cradle Charge Methods



Cradle options

3-slot cradles





3-Slot Cradles:

CRD-MC18-3SLOTH-01

3-Slot Non-Locking High Density Cradle, display facing out. Compatible with MC18 and PS20.

CRD-MC18-3SLCKH-01

3-Slot Locking High Density Cradle, display facing out. Compatible with MC18 and PS20.

CRD-MC18-3SLCKS-01

3-Slot Locking Super High Density Cradle, display facing up. Compatible with MC18 and PS20.

All cradles require: Power Supply PWR-BGA12V108W0WW, DC line cord and Country Specific AC line cord sold separately.

Additional accessories for single slot cradle



PWR-BGA12V108W0WW

Level VI AC/DC power supply. AC Input: 100-240V, 2.8A. DC Output: 12V, 9A, 108W. Requires: DC line cord and country specific grounded AC line cord.

CBL-DC-394A1-01



DC Line Cord 19.5inch (0.5M) for powering one cradle from a single power supply. Supports interconnected cradles to charge maximum 6 devices depending on charging mode required.

CBL-DC-393A1-02



DC "Y" Line Cord 39.7inch (1M) for powering two cradles from a single power supply. Supports interconnected cradles to charge maximum 12 devices (up to 6 devices powered off each leg of the cable) depending on charging mode required.

CBL-DC-392A1-02



DC "Y" Line Cord 79.4inch (2M) for powering two cradles from a single power supply. Supports interconnected cradles to charge maximum 12 devices (up to 6 devices powered off each leg of the cable) depending on charging mode required.

25-66430-01R



Cradle Interconnection Cable 60 Inch (1.5M) Connects Cradles to each other to run off one power supply.

25-66431-01R



Cradle Interconnection Cable 12.6 Inch (32cm) Connects Cradles to each other to run off one power supply

CBL-MC18-EXINT1-01



Cradle Interconnection Extension Cable 12.6 Inch (32cm). Connects two Interconnection cables 25-66431-01R together to provide additional length.

3-Slot Cradle Charge Methods

Step 1: Power Supply	Step 2: Charge Mode		Step 3: DC Line Cord	
Level VI power supply PWR- BGA12V108W0WW and country	Choose required charging mode.	Select one DC Cable to connect a power supply to multiple 3-s cradles depending on charge mode:		
specific 3-wire AC Line Cord.	Fast – 1.5 AMPS: MAX: 3 x 3-Slot Cradles,	CBL-DC- 394A1-01	DC Line Cord 19.5inch (0.5M). Supports up to two 3-slot cradles.	
	total of 9 Devices	CBL-DC- 393A1-02	DC "Y" Line Cord 39.7inch (1M). Supports up to four 3-slot cradles (max 2 cradles powered off each leg of the cable)	
	Standard - 1.0 AMP: MAX: 4 x 3-Slot Cradles, total of 12 Devices	CBL-DC- 392A1-02	DC "Y" Line Cord 79.4inch (2M). Supports up to four 3-slot cradles (max 2 cradles powered off each leg of the cable)	
Step 4: Interconnect cables				
Choose the number of cradle interconnect cables required based on charge mode and following the table below.				

Fast Charge Mode

3 Three-Slot Cradles Maximum per power supply. No more than 2 cradles can be powered off each leg if a "Y" power cable is used.



 \mathcal{D}

Cradle Interconnect Cables 25-66431-01R (12.6inch, 32cm)

Interconnection Extension Cable (12.5inch, 32cm): CBL-MC18-EXINT1-01

Number of Cradles	2	3
# of Interconnect Cables required	1	1
# of Extension Cables required	2	3

Standard Charge Mode


4 Three-Slot Cradles Maximum per power supply. No more than 2 cradles can be powered off each leg if a "Y" power cable is used.

Cradle Interconnect Cables 25-66431-01R (12.6inch, 32cm)

Interconnection Extension Cable (12.5inch, 32cm): CBL-MC18-EXINT1-01


Number of Cradles	2	3	4
# of Interconnect Cables required	1	1	2
# of Extension Cables required	2	3	4

3-Slot Cradle Charge Methods



Other cradle accessories





Other PS20 accessories

USB Programing Cable



CBL-PS20-USBCHG-01

PS20 USB cable, also allows USB communication to the device when connected to a PC.

Cart Mount



PSS-3SH01-00R

Cart mount, allows mounting the PS20 mobile computer on a shopping cart, it also allows to use the device on hands-free scanning mode.

Soft Holster



SG-PS20-SFTHLT-01

PS20 Soft Holster, allows to wear the device on the hip (includes belt clip) or crossbody with an additional shoulder strap (part number 58-40000-007R).

Screen Protector



MISC-PS20-SCRN-05 PS20 Tempered glass screen protector (Qty. 5)

Other accessories

Country specific 3-wire AC line cords

Part Number	Description
23844-00-00R	AC line cord, 7.5 feet long, grounded, three wire. Associated Country: US
50-16000-217R	AC Line Cord, 1.9M, grounded, three wire, AS 3112 plug. Associated Country: Australia, New Guinea
50-16000-218R	AC Line Cord, 1.8M, grounded, three wire, NEMA 1-15P plug. Associated Country: Japan
50-16000-219R	AC Line Cord, 1.8M, three wire, grounded BS1363 plug. Associated Countries: Hong Kong, Iraq, Malaysia, Singapore, United Kingdom
50-16000-220R	AC Line Cord, 1.8M, grounded, three wire CEE 7/7plug. Associated Countries: Europe, Abu Dhabi, Bolivia, Dubai, Egypt, Iran, Korea, Russia, Vietnam
50-16000-256R	AC Line Cord, 1.8M, grounded, three wire, CEE7/7 plug. Associated Country: Korea
50-16000-257R	AC Line Cord, 1.8M, grounded, three wire, IEC 60320 C13 plug. Associated Country: China
50-16000-669R	AC Lind Cord, 1.9 M grounded, three wire, BS 546 Plug. Associated Country: India
50-16000-671R	AC Line Cord, 1.8M grounded, CIE 23-16 plug. Associated Country: Italy
50-16000-672R	AC Line Cord, 1.9M grounded, three wire, S132 Plug. Associated Country: Israel
50-16000-727R	AC Line Cord, 1.9M grounded, three wire. Associated Country: Brazil