

## **Mobile Computer**











WiFi



Bluetooth



1D Barcode



2D Barcode



PSAM



NFC



Camera



This device is an Android rugged mobile computer. With this mobile computer in your hand, you can find this easy-todeploy device an exceptionally valuable helper for your workers to increase your efficiency and productivity. It can be deployed in many areas, like logistics, warehouse management, asset tracking, fleet management, healthcare and etc.















## **Specification**

Physical Characteristics			
Dimensions	157.6 x 73.7 x 29mm/6.2x2.9x1.1in		
Weight	292g/10.3oz		
Display	4" WVGA (480*800), 16.7M colors		
Touch Panel	Rugged dual touch capacitive touch panel		
Power	Main battery: Li-ion, rechargeable, 4200mAh		
	Standby: over 300 hours		
	Continuous use: over 12 hours (depending on user environment)		
	Charging time: 3-4 hours (with standard adaptor and USB cable)		
Expansion Slot	1 PSAM (only for high-level configuration,but is not available for V4 version): ISO7816 protocol ,1 SIM, 1 MicroSD (TF) slot		
Interfaces	USB Micro-B, OTG		
Audio	0.5W speaker, build-in microphone		
Keypad	3 TP soft keys, 3 side keys, numeric keyboard		
Sensors	Light sensor, proximity sensor, gravity sensor, vibration motor		
Performance			
High-level Configuration	CPU: Cortex A-53 1.3 GHz quad-core		
	RAM+ROM: 2GB+16GB		
Low-level Configuration	CPU: Cortex A-53 1.3 GHz quad-core		
	RAM+ROM: 1GB+8GB		
Expansion	Supports up to 128 GB Micro SD card		
Developing Environment			
Operating System	Android 6.0		
SDK	Software Development Kit		
Language	Java		
Tool	Eclipse / Android Studio		
User Environment			
Operating Temp.	-4°F to 122°F / -20°C to 50°C		
Storage Temp.	-40°F to 158°F / -40°C to 70°C		
Humidity	5%RH - 95%RH non condensing		
Drop Specification	Multiple 2m/6.56ft drops to concrete across the		
	operating temperature range		
Tumble Specification	1000 x 0.5m/1.64ft falls at room temperature		
Sealing	IP65 per IEC sealing specifications		
ESD	±15KV air discharge, ±6KV conductive discharge		

Communicat	ion
WLAN	IEEE802.11 a/b/g/n, 2.4G/5G dual-band, internal antenna
WWAN(Europe)	2G: 850/900/1800/1900MHz
	3G: 850/900/1900/2100MHz
	4G: B1, B3, B5, B7, B8, B20, B40
WWAN(America)	2G: 850/900/1800/1900MHz
	3G: 850/900/1700/1900MHz
	4G: B2, B4, B7, B12, B17
WWAN (China)	2G: 900/1800MHz
	3G: 900/1900/2000/2100MHz
	4G: B1, B3, B38, B39, B40, B41
WWAN (V4)	2G: 850/900/1800/1900MHz
	3G: WCDMA: B1, B2, B4, B5, B8
	4G: TDD-LTE: B38, B39, B40, B41
	FDD-LTE: B1, B2, B3, B4, B5, B7, B8, B12, B17, B20
WWAN (Others)	Depending on the country's ISP
Bluetooth	Bluetooth 4.0, BLE
GNSS	GPS/AGPS, GLONASS, BeiDou, internal antenna
Data Collecti	on
Camera	
Camera	8/13MP Autofocus with flash
Barcode Sca	nning (Optional)
1D Linear Scann	er
1D Scan Engine	Zebra SE965 / Honeywell N4313 / UE966
Symbologies	UPC/EAN, Code128, Code39, Code93, Code11, Interleaved 2 of 5, Discrete 2 of 5, Chinese 2 of 5, Codabar, MSI, RSS, etc.
2D Imager Scan	ner
2D CMOS Laser Scanner	Zebra SE4710/SE2100/Honeywell N6603
Symbologies	PDF417, MicroPDF417, Composite, RSS, TLC-39, Datamatrix, QR code, Micro QR code, Aztec, MaxiCode; Postal Codes: US PostNet, US Planet,

Postal (KIX), etc.

13.56MHz

UK Postal, Australian Postal, Japan Postal, Dutch

ISO14443A/B, ISO15693, NFC-IP1, NFC-IP2, etc.

M1 card (S50, S70), CPU card, NFC tags, etc.

## Accessories(See details in Accessory Guide)



AC Adapter USB cable



Charging Cradle (only optional for high-level configuration)



**NFC** 

Frequency

Protocol Chips

8-slot Battery Charger









Wristband

Holster

 $<sup>^{\</sup>ast}$  NFC is only available for high-level configuration, and pistol grip is only available for V4 version, NFC can not coexist with the pistol grip