



PC55 Price Checker Kiosk (1D/2D)

The PC55 is an entry level, small and attractive price checker featuring the latest technology with interface options such as Wireless RF or hard wired Ethernet.

Depending on the font set, the bright and vivid screen can display up to 20 characters per line. There is a choice of bar code scanners between the entry level single scan line CCD scanner and the high performance 24 scan lines omni-directional laser scanner (2D scan engine is also available per customers request).

Because of its size and the sleek good looks, the PC55 can be installed anywhere in a store including on the shelves; this flexibility of installation is enhanced by the optional Power-over-Ethernet.

Main Features:

- Driven by Linux OS
- 3.5" color display
- Self detection and configuration of scan-engine at start-up
- Choice of scanner: Laser Omni/CCD Single Line/2D imager
- Choice of Interface: Ethernet/WiFi/Power over Ethernet
- +5V power supply
- Wall mounting by 2 screws
- Simple configuration by standard web browser

System

Processor	ARM Cortex-A7 Dual-Core
Operating Platform	Standard Linux (Kernel > 3.0)
Memory Flash	4GB, expandable with USB ash drive and USD card
Memory RAM	512MB
Software	Client applications included

Output Media

Display	3.5" diagonal
Brightness	450 nits 16 million colors for high quality displaying
Resolution	320 x 240 pixels
Graphics Supported	PNG, JPEG, GIF, BMP
Speaker	1 Speaker

Power Requirements

Power Supply	+5V/2A PSU or Power over Ethernet (IEEE802.3af)
Power Consumption	3-5Watt (5Vdc, 580~1050mA) Depending on interface and scanner type.

Physical

Dimensions (H x W x D)	182 x 131 x 95mm (7.17 x 5.16 x 3.74 inch)
Weight	0.9 kg (2 lb)
Mounting Options	Wall mount with 2 screws

Data Ports

USB 2.0	x 1
LAN port 10/100 MB	x 1
Power Over Ethernet Module	Optional
Entry/Exit Gate Control Function GPIO	Optional (2-pin conn)

Network Interface

Wired LAN	* Ethernet :100MB Base-TX/10MB Base-T(802.3) standard on board * Power over Ethernet IEEE 802.3 af optional
Wireless LAN	802.11 a/b/g/n/ac 2.4G/5GHz
Encryption Protocols	WPA, PSK and WPA Enterprise security

Data Input

Scanner Possibilities

Omni Directional Laser Scanner :

High Speed, hi sensitive and omni-directional scanning. Reading of fragmented bar codes. Visible laser diode 635nm.
Scan pattern: 6 direction scan field, 24 lines.
Scan rate: 2000 scans/sec
Up to 300mm@UPC/EAN 100%, PCS90%

CCD Scanner:

Smart detect up to 500 scans/sec

2D Imager:

Visible Red light 650nm
Scan rate: 200 scans/sec auto adaptive in linear mode, 56 images/sec auto adaptive 2D mode.
Resolution: 752 Hor. X 480 Vert. pixels, 256 gray levels.

Omni Directional Laser Scanner :

EAN/UPC/JAN+Add-on,ISBN,Code 128,EAN128, Code 93, Code39, Code32, Codabar,Interleaved 2 of 5, MSI-Plessey and GS1 DataBar.

CCD Scanner:

All UPC/EAN/JAN, EAN128 Code, Code 39, Code 39 Full ASCII Code32 / Italian Pharmacy, Code 128, CODABAR/NW7,Interleave 25, Industrial 25, Matrix 25, MSI/PLESSEY, Telepen Code 93, Code 11, China Postage, Code 26, LCD25 and GS1 DataBar Family.

2D Imager:

1D Symbologies: EAN/UPC,Australian Post, Aztec, BPO, Canada Post, Dutch Post, EAN, UCC Composite, Interleaved 2 of 5, Japan Post, MSI Code, Planet, Plessey Code, Postnet, GS1 Databar, Standard 2 of 5, Telepen, TLC39
2D Symbologies: Datamatrix, Matrix 2 of 5, Maxi 2 of 5, Maxicode, QR code

Symbologies Supported

Environmental

Operating Temperature	0° ~ 40°C (32° ~ 104°F)
Storage Temperature	-20° ~ 60°C (-4° ~ 140°F)
Humidity	5%~95% RH (non-condensing)

Regulatory

CE, FCC and RoHS compliant

Specifications subject to change without notice.

Copyright 2014 Unitech Electronics Co., Ltd.
All rights reserved. Unitech is a registered trademark of Unitech Electronics Co., Ltd.

All product and company names are trademarks, service marks, or registered trademarks of their respective owners.

unitechbarcode.com

Unitech America, Inc. | 6182 Katella Avenue | Cypress, CA 90630
714-891-6400 ph | 800-861-8648 toll | 714-891-5050 fx